59383 U.S. PTO
08791057
01/13/97



FIG 1

Figure 1 Thermodynamic representation of the effect of high-entropy fluid removal on compression efficiency



FIG 2

Figure 2 Fractional reduction in work(or fractional increase in efficiency) per fraction of fluid removed.

59383 U.S. PTO
08/791057
01/13/97



FIG 3



FIG 4

SUBSTITUTE SHEET (RULE 26)

[redacted]

59383 U.S. PTO
08791057
01/13/97



FIG 5

Figure 5 Illustrating fluid removal ahead of shock impingement

59383 U.S. PTO
08791057
01/13/97



FIG 6

Axial view



FIG 7.

Tangential view

Illustrating fluid removal near trailing edge of suction surfact at blade tip, to negate clearance vortex blockage.

SUBSTITUTE SHEET (RULE 26)

5 83 U.S. PTO [redacted]
791057
01/13/97



FIG 9



FIG 10



FIG. 8

[redacted]

59383 U.S. PTO
08791057
01/13/97



FIG 11

Figure 11 Variation with radius of ratio of blade-relative stagnation pressure to passage pressure



FIG 12

Axial view

59383 U.S. PTO
08791057
01/13/97



Tangential view

Fig 13

59383 U.S. PTO
08791057
01/13/97



FIG 14

Figure 14 Schematic arrangement of counter-rotating compressor with stationary blade rows upstream and downstream of counter-rotating pair..

SEP 25 1996



FIG 15

Figure 15. Velocity triangles for counter-rotating compressor with inlet and exit stator blades, and balanced diffusion in the two rotors.